

WIRELESS ADS DIMMER

Wi-Fi Single Input Controller

Models: ACM-1D-2Z

Data Sheet Rev 3.2







OVERVIEW

The ADS Dimmer is a Wi-Fi enabled universal dimmer module with remote control capability over the internet via the TIS app. This product features dry input(s) particularly designed to be coupled with any push-button wall switch for smart lights control.

KEY BENEFITS

- Compatibility with other TIS solutions
- Smooth Wi-Fi connectivity
- Applicability for most types of lights
- Budget-friendly product to make homes smart

KEY FEATURES

- Equipped with 2 digital inputs
- Programmable for scenes & presets
- Efficiency in installation time & cabling
- Controllable via TIS App











WIRELESS ADS DIMMER

Wi-Fi Single Input Controller


Models: ACM-1D-2Z





		PRODUCT SPECIFICA	TIONS	
4	Power supply	Input voltage Output power Protection Current consumption	110-230 VAC 50/60 Hz 3W / 12V Internal protection fuse 10-20 mA / 12 V DC	
Ţ	Output	Number of channels Nominal voltage Nominal current per channel Lighting incandescent lamp LED (dimmable) CFL (dimmable)	1 110 / 230 V AC 50/60 Hz 500 Watts 300 Watts 300 Watts	
τιςÂÎR	TIS AIR	WIFI signal Protocol standard	2.4 GHz 802.11 b/g/n	
(Reaction time		approx. 30ms	
Îo	Mounting	Free locate	Can be installed anywhere	
† ! †	Operation	Digital inputs TIS AIR PRG button with LED Upgrading	2 dry inputs for lights control TIS protocol messages & commands For Programming Over WIFI connection	
å	Weight	Without packaging	10g	
1	Dimensions	(Width \times Length \times Height)	20mm × 49mm × 49mm	
	Housing	Materials Internal parts color IP rating	Fireproof PC White IP 50	
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C	
	Air humidity		<80% non-condensing	





----20mm-----

