

TIS PANEL ADDITION

3 Digital Inputs with 12V Power supply

Data Sheet Rev 3.2

Model: ADD-3DL-12V







OVERVIEW

This bus-operated device is attached to the back of TIS wall switches to complete their installment and expand their functions. It features three digital inputs for integration with sensors, and is capable of supplying 12V power for motorized devices.

KEY BENEFITS

- Adds 3rd party devices to TIS network
- Makes traditional light switches smart
- Improves home security system.
- Suuplies 12V power to 3rd party sensor

KEY FEATURES

- ★ Works with TIS BUS protocol
- Equipped with 3 digital inputs
- Capable of motorized functions & scene creation
- Attachable to TIS wall switches













TIS PANEL ADDITION
3 Digital Inputs with 12V Power Supply Model: ADD-3DL-12V



	PRODUCT SPECIFICATIONS		
Ţ	Input	Number of channels Input Type Length of connected wire	3 Digital input. Open / Close < 350 meter
Ţ	Output	Low Voltage	12V DC 100mA
•	Protection	Bus connection Digital input	Reverse Polarity Protection Low voltage <24V Protection
o _o	Function programmable options	Digital input Open Digital input close Revers control	20 commands 20 commands 1 command
Îo	Mounting	Behind the panel	Attachable to the back of TIS panels Fits in all types of standard back boxes
	Connection terminal	Load and Power Data / bus Panel Link	Screw terminal 0,252mm2 Connectors Link Female 2 connectors for TIS Panel connection
å	Weight	Without packaging	20 G
+	Dimensions	Width \times length \times height	54mm × 50mm × 24mm
	Housing	Materials Casing color IP rating	Fire-proof PC White IP 20
1	Temperature range	Operation Storage Transport	-3060°C -2060°C -3075°C
	Air humidity		<85% non-condensing

50mm GND D- D+ +24V PANEL ADDITION Model : ADD-3DL-12V +12V GND Z3 Z2 Z1



