

## **WIRELESS ADS DIMMER**

Wi-Fi Single Dry Input Controller

Models: ADS-1D-1Z







## **OVERVIEW**

This product is WiFi-operated dimmer module designed to convert a traditional light or curtain switch into a smart one with the capability for remote control.

### **KEY BENEFITS**

- Compatibility with other TIS solutions
- Smooth Wi-Fi connectivity
- Applicability for most types of lights
- Budget-friendly product to make homes smart

#### **KEY FEATURES**

- Equipped with 1 digital inputs
- Programmable for scenes & presets
- Efficiency in installation time & cabling
- Controllable via TIS App.














# **WIRELESS ADS DIMMER**



Models: ADS-1D-1Z





		PRODUCT SPECIFICA	TIONS
*	Power supply	Input voltage Output power Protection Current consumption	110-230 VAC 50/60 Hz 3W / 12V Internal protection fuse 10-20 mA / 12 V DC
Ţ	Output	Number of channels Nominal voltage Nominal current per channel Lighting incandescent lamp LED (dimmable) CFL (dimmable)	1 110 / 230 V AC 50/60 Hz 500 Watts 300 Watts 300 Watts
TISÂÎR	TIS AIR	WIFI signal Protocol standard	2.4 GHz 802.11 b/g/n
( <del>)</del>	Reaction time		approx. 30ms
<b>T</b> o	Mounting	Free locate	Can be installed anywhere
† <del>!†</del>	Operation	Digital inputs TIS AIR PRG button with LED Upgrading	dry input for lights control     TIS protocol messages & commands     For programming     Over WIFI connection
å	Weight	Without packaging	10g
<b>+</b>	Dimensions	(Width $\times$ Length $\times$ Height)	35mm × 50mm × 50mm
	Housing	Materials Internal parts color IP rating	Fireproof PC White IP 50
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
8	Air humidity		<80% non-condensing

