

## TIS IO OUTDOOR BELL PANEL

Hotel Panel with Room Number Display

Data Sheet Rev 3.2

Model: IO-OUT-HOTEL





### **OVERVIEW**

This product features a bell panel with room number display and touch buttons for room services designed for maximum conveniene and efficiency in hospitality facilities.

#### **KEY BENEFITS**

- Upgraded hospitality convenience
- Practical features in fashionable design
- High-end guest room management
- ♣ Applicable in hotels, resorts, clubs, etc

#### **KEY FEATURES**

- Bell button & room number display
- Touch buttons for DND & MUR.
- Customizable RGB backlits
- Available in black & white







# TIS IO OUTDOOR BELL PANEL

Hotel Panel with Card Readability
Model: IO-OUT-HOTEL





PRODUCT SPECIFICATIONS			
<u>+</u>	Input	Dry Inputs	4 Digital Inputs
<u></u>	Output	Low current relay	1 Relay Output 2A/12V
TISBUS	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
<b>Ø</b>	Protection		Reverse Polarity Protection ESD Protection
( <del>)</del>	Reaction time		approx. 20ms
To	Mounting	Wall mount	by 2 screws on the back box (UK, EU, US)
===	Connection terminal	Data	2 male pins connectors to fit in panel addition
†‡†	Operation	Push buttons Backlight TIS bus Upgrading	1 push button with red / white indicator 2 RGB indicators + Room number white LEDs TIS Protocol messages and commands By Rs485 upgrading kit
<b>Q</b> O	Functions	Bell Press	Push button
۵	Weight	Without packaging	120g
<b>+</b>	Dimensions	Width $\times$ Length $\times$ Height	94mm× 13mm × 129mm
	Housing	Materials Casing color Internal Parts color IP rating	PC fire proof / acrylic in front Silver plating frame. Glass black Black & White IP 50
	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
<b>&amp;</b>	Air humidity		<80% non-condensing





