



TIS LUNA 9G PANEL

9-Gang Touch Panel

Data Sheet Rev 3.2

Model: LUNA-9G



OVERVIEW

This product is a BUS-operated wall panel with touch buttons for smart control over lights, curtains, and preset scenarios. It comes in black and white and customizable RGB lights for maximum aesthetics.

KEY BENEFITS

- ➕ Compatible with other TIS solutions
- ➕ Ideal for smart lights ON/OFF/dimming
- ➕ Capable of setting motorized curtains
- ➕ Smooth & automatic scene activation

KEY FEATURES

- ★ Nice interface with high sensitivity
- ★ TIS remote control compatibility
- ★ Programmable for scenes & presets
- ★ Controllable via TIS App



TIS LUNA 9G PANEL
















9-Gang Touch Panel


Model: LUNA-9G



TIS

PRODUCT SPECIFICATIONS

	Touch	Active area Touch Type	4.3" Capacitive
	Input	IR receiver Using Panel Addition	IR receiver Using Panel Addition
	Output	Using Panel Addition 3R Using Panel Addition 3DL-12V Using Panel Addition 2DL-IRE	3 Relay Output 3A/5A 12V DC 50mA Output IR Emitter
	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <45 mA / 24 V DC
	Protection		Reverse Polarity Protection ESD Protection
	Reaction time		approx. 20ms
	Mounting	Wall mount	by 2 screws on the back box (UK, EU, US)
	Connection terminal	Data	2 male pins connectors to fit in panel addition
	Operation	Touch buttons Backlight TIS bus Upgrading	9 buttons 8 RGB indicators TIS Protocol messages and commands By Rs485 upgrading kit
	Functions	1 Press Long Press Double click IR receiver	ON/OFF/Scene Dim or ramp the lights Extra Scene Music, scene, lights control
	Weight	Without packaging	180g
	Dimensions	Width × length × height	94mm × 129mm × 13mm
	Housing	Materials Casing color Internal Parts color IP rating	Fireproof PC / Glass in front Silver plating frame. Glass white or black Black & White IP 50
	Temperature range	Operation Storage Transport	-10...60°C -20...50°C -25...75°C
	Air humidity		<80% non-condensing



Copyright © 2022 TIS, All Rights Reserved

TIS Logo is registered trademark of TIS CONTROL .
All of the specification are subject to change without notice.

TIS CONTROL PTY LIMITED
SA , AUSTRALIA

TIS CONTROL LIMITED
Wanchai, Hong Kong

www.tiscontrol.com