

## **TIS LUNA TFT PANEL**

4.3" Touch Panel Model: LUNA-TFT43

Data Sheet Rev 3.2







### **OVERVIEW**

This product is a BUS-operated wall panel with touch buttons for smart control over lights, curtains, indoor climate, appliances, and preset scenarios. This switch is remotely controllable and applicable in various types of buildings.

#### **KEY BENEFITS**

- Compatible with other TIS solutions
- TFT LCD in trendy black/white finishes
- Smooth & automatic scene activation
- + Full control over home, hotel & office rooms

#### **KEY FEATURES**

- Nice interface with high sensitivity
- Easy-to-navigate setting layouts
- ★ Programmable for scenes & presets
- ★ Controllable through TIS App













## TIS LUNA TFT PANEL 4.3" Touch Panel

Model: LUNA-TFT43





PRODUCT SPECIFICATIONS				
	LCD	Size Resolution Contrast Viewing direction	3.5" 320*480 Pixels 500 160 degree	
2	Touch	Active area Touch Type	4.3" Capacitive	
<u>+</u>	Input	Temp sensor IR receiver Using Panel Addition	Resistive Temp Sensor TIS Infrared code receiver 2-3 Digital Input	
<u>.</u>	Output	Using Panel Addition 3R Using Panel Addition 3DL-12V Using Panel Addition 2DL-IRE	3 Relay Output 3A/5A 12V DC 50mA Output IR Emitter	
TISBUS	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <80 mA / 24 V DC	
<b>9</b>	Protection		Reverse polarity protection ESD Protection	
<b>(</b> )	Reaction time		approx. 20ms	
To	Mounting	Wall mount	by 2 screws on the back box (UK, EU, US)	
===	Connection terminal	Data	2 male pins connectors to fit in panel addition	
†‡†	Operation	LCD touch buttons Backlight TIS bus Upgrading	TFT full color 5 buttons for menu selection 2 White indicators TIS protocol messages and commands By Rs485 upgrading kit	
o <sub>o</sub>	Functions	1 Press Long Press Double click IR receiver	ON/OFF/Scene Dim or ramp the lights Extra Scene Music, scene, lights control	
Ĝ	Weight	Without packaging	200g	
+	Dimensions	Width × length × height	94mm × 129mm × 13mm	



# TIS LUNA TFT PANEL 4.3" Touch Panel

Model: LUNA-TFT43





PRODUCT SPECIFICATIONS				
	Housing	Materials Casing color Internal Parts color IP rating	Fireproof PC / Glass in front Silver plating frame. Glass white or black Black & White IP 50	
<u>.</u>	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C	
8	Air humidity		<80% non-condensing	





