

TIS DIGITAL INPUT MODULE

Dry Input with 4 Zones

Data Sheet Rev 3.2

Model: TIS-4DL-IN





OVERVIEW

This product is designed to make traditional light switches smart without the need for further cabling, and integrate third-party devices into building's automation system.

KEY BENEFITS

- Compatibility with other TIS solutions
- Better reliability & more flexibility
- Easy communication & faster response time
- Improving home security system.

KEY FEATURES

- 4 digital inputs for automation & security
- Small size, applicable everywhere
- Open/Close digital inputs
- Reverse polarity protection









TIS DIGITAL INPUT MODULE

TIS

Dry Input with 4 Zones Model: TIS-4DL-IN



PRODUCT SPECIFICATIONS			
<u>+</u>	Input	Number of channels Input Type Length of connected wire	4 Digital input. Open / Close < 350 meter
(TISBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <12 mA / 24 V DC
3	Protection	Bus connection Digital input	Reverse Polarity Protection Low voltage <24V Protection
()	Reaction time		approx. 20ms
Îo	Mounting	anywhere	by two screws
1000	Connection terminal	Data / bus	Screw terminal 0.252.5mm2
†‡†	Operation	Programming button/LED By TIS bus Upgrading	For assignment of the physical address TIS Protocol messages and commands 1 X mini USB for upgrading
o o	Functions for each zone	Digital input Open Digital input close Revers control	20 commands 20 commands 1 command
å	Weight	Without Packaging	100g
+	Dimensions	Width × Length × Height	16mm × 46mm × 46mm
	Housing	Materials Casing color IP rating	Fireproof ABS Dark / Gray IP 20
l	Temperature range	Operation Storage Transport	-1050°C -2050°C -2575°C
8	Air humidity		<85% non-condensing



