

## TIS TEMPERATURE SENSOR

Smart Sensor with Multi-zone Function

Data Sheet Rev 3.2

Model: TIS-4T-IN





### **OVERVIEW**

This product records, monitors, and sends signals for changes in temperature across four different zones around home with high responsiveness and precision to bring the maximum user comfort and energy efficiency.

#### **KEY BENEFITS**

- Compatibility with other TIS solutions
- Maximum energy optimization
- Constant temperature level adjustment
- Prevention of mold and bacteria

#### **KEY FEATURES**

- Automatic temperature alert notifications
- 4 separately controllable thermal zones
- Compatibility with PTC1000 sensors
- Controllable via TIS App















# TIS TEMPERATURE SENSOR



Temperature Sensor with 4 Zones Model: TIS-4T-IN



		PRODUCT SPECIFICATIONS	
<u>+</u>	Input	4× Temperature Inputs	TIS temperature sensor or PTC1000 sensor
TISBUS	TIS BUS	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <15 mA / 24 V DC
<b>Ø</b>	Protection	Bus connection Sensor inputs	Reverse Polarity Protection Reverse Polarity Protection
( <del>)</del>	Reaction time		approx. 20ms
ĵo	Mounting	Anywhere	by two screws
	Connection terminal	Data / BUS	Screw terminal 0.252.5mm2
† <del>!†</del>	Operation	Programming button/LED By TIS bus Upgrading	For assignment of the physical address TIS Protocol messages and commands 1 × mini USB for upgrading
<b>\$</b> 0	Functions	Temperature logic	Send command if temperature in specific range
۵	Weight	Without packaging	100g
+	Dimensions	(Width $\times$ Length $\times$ Height)	16mm × 46mm × 46mm
	Housing	Materials Internal Parts color IP rating	Fireproof ABS Black / Gray IP 20
	Temperature range	Operation Storage Transport	-1050°C -2050°C -2575°C
	Air humidity		<85% non-condensing





