

TIS MERCURY OUTDOOR BELL PANEL

Data Sheet Rev 3.1


Outdoor hotel bell panel with RF Model: TIS-MER-HTL-RF



OVERVIEW

CEROHS C C FC

Our Mercury Outdoor Bell Panel serves as both an RF card reader and an access control system. Additionally, it features indicators for hotel services, including Do Not Disturb (DND) and Make Up Room (MUR).






TIS MERCURY OUTDOOR BELL PANEL

Outdoor hotel bell panel with RF Model: TIS-MER-HTL-RF



T || \$

PRODUCT SPECIFICATIONS			
Ļ	Input	RF card reader Using Panel Addition	Mayfair RF Type 2 Dry Inputs
1	Output	Using Panel Addition	1-3 Relay 2A output
(TISBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <25 mA / 24 V DC
۲	Protection	Protection	Reverse Polarity Protection ESD Protection
Q.	Reaction time		approx. 20ms
Î	Mounting	Wall mount	by 2 screws on the back box (UK, Europe)
800	Connection terminal	Data	2 male connectors pins to fit in panel addition
ţţţ	Operating and display elements	Backlight TIS bus Upgrading	2 RGB indicators + Room number white LEDs TIS Protocol messages and commands By Rs485 upgrading kit.
Ô	Weight	Without packaging	89 g
÷	Dimensions	Width \times length \times height	86mm × 86mm × 10mm
	Housing	Materials Casing color Internal Parts color IP rating	PC anti fire / Glass in front Aluminum frame Black IP 50
l	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
٨	Air humidity		<80% non-condensing



TIŜ

Copyright © 2025 TIS, All Rights Reserved TIS Logo is registered trademark of TIS CONTROL. All of the specification are subject to change without notice. TIS CONTROL PTY LIMITED SA, AUSTRALIA TIS CONTROL LIMITED Wanchai, Hong Kong

www.tiscontrol.com