
TIS SIRIUS PANEL

2 Buttons

Data Sheet Rev 3.1

Model: TIS-SIR-2G






OVERVIEW

We are proud to present the Sirius series, a testament to our commitment to combining elegant classical design with advanced smart technology. Designed with discerning customers in mind, the sirius series offers sophisticated aesthetics and seamless functionality, making it the perfect choice for smart hotels and modern homes alike.

KEY BENEFITS

- Control your lights, dimmers and RGB color.
- Elegant classical design
- Stylish labeled backlit flush mount Buttons:
- Customizable options



KEY FEATURES

- Wall mount, push buttons
- Works with TIS-BUS protocol
- Available in three different colors
- Fit in UK back box standard



BARCODE (UPC-A)

0 606795 210831

BARCODE (UPC-A)

0 606795 210848

TIS SIRIUS PANEL

2 Buttons


Model: TIS-SIR-2G





PRODUCT SPECIFICATIONS

TISBUS	**TIS Bus**	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <35 mA / 24 V DC
	Protection		Reverse Polarity Protection ESD Protection
	Reaction time		approx. 20ms
	Mounting	Wall mount	by 2 screws on the back box (UK, Europe, US)
	Connection terminal	Data	2 male pins connectors to fit in panel addition
	Operating and display elements	2 Buttons Indicator LED TIS bus	For controlling lights, scene, etc… 2 White and Orange LED TIS Protocol messages and commands
	Functions	1 Press Long Press Double click	ON/OFF/Scene Dim or ramp the lights Extra Scene
	Weight	TIS-SIR-2G	98 g
	Dimensions	TIS-SIR-2G	85mmx85mmx25mm
	Housing	Materials Casing Color Options IP rating	PC anti fire Aluminum Gold or Gray Stainless Steel Black or White IP 30
	Temperature range	Operation Storage Transport	-10…60°C -20…50°C -25…75°C
	Air humidity		<85% non-condensing



TIS-SIR-2G

Copyright © 2024 TIS, All Rights Reserved
TIS Logo is registered trademark of TIS CONTROL.
All of the specification are subject to change without notice.

TIS CONTROL PTY LIMITED
SA, AUSTRALIA

TIS CONTROL LIMITED
Wanchai, Hong Kong