

TIS TITAN / TITANIA SERIES

2.4" Touch Switch

Data Sheet Rev 3.2

Model: TIT-TFT-BUS-K(3R), TIT-TFT-BUS-S(3R)



OVERVIEW

This product is a wall switch with touch LCD and buttons designed for lights, climate, music, security, and motorized curtains control. It offers customizable backlit color and frame covers for an easy combination with interior schemes.



TIS TITAN / TITANIA SERIES

2.4" Touch Switch Model: TIT-TFT-BUS-K(3R), TIT-TFT-BUS-S(3R)



		PRODUCT SPECIFICA	CIFICATIONS		
	LCD	Size Resolution Contrast Viewing direction	2.4" 240*320 Pixels 600 120 degree		
£	Touch	Active area Touch type	2.5" Capacitive		
÷	Input	Temp sensor Dry inputs	Resistive temp sensor 2 Digital inputs		
Ť	Output	Model with relay -3R	3 Relay outputs 5A		
(TI SBUS)	TIS Bus	Number of devices on 1 line Bus voltage Current consumption	Max. 64 12-32 V DC <60 mA / 24 V DC		
۲	Protection		Reverse polarity protection ESD Protection		
().	Reaction time		approx. 20ms		
ĵo	Mounting	Wall mount	with 2 screws on the back box (UK, US)		
1993 1993	Connection terminal	Data and digital inputs Relay channels	6 pushing pin type 1.5mm 4 pushing pin type 2.5 mm		
†∔†	Operation	LCD Touch buttons Backlit TIS bus Upgrading	TFT full color 2 touch buttons for menu selection 2 LED indicators TIS protocol messages & commands Rs485 upgrade kit		
¢o	Functions	1 Press Long press Double click	ON/OFF/Scene Adjust lights brightness Extra scene		
۵	Weight	Without packaging	200g		
Ŧ	Dimensions (Width × Length × Height)	Titan with the cover Titania with the cover	29mm × 90mm × 86mm 29mm × 66mm × 110mm		



Copyright © 2022 TIS, All Rights Reserved TIS Logo is registered trademark of TIS CONTROL. All of the specification are subject to change without notice. TIS CONTROL PTY LIMITED SA , AUSTRALIA **TIS CONTROL LIMITED** Wanchai, Hong Kong

TRIS

www.tiscontrol.com

TIS TITAN / TITANIA SERIES

2.4" Touch Switch Model: TIT-TFT-BUS-K(3R), TIT-TFT-BUS-S(3R)



TIŜ

	PRODUCT SPECIFICATIONS		
] Housing	Materials Casing color Internal Parts color IP rating	Fireproof PC / Glass in front Aluminum, glass, or plastic frame Black IP 50	
Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C	
Air humidity		<80% non-condensing	
<mark>Titan TFT panel</mark> TIT-TFT-BUS-K-(3R)	TIS Wall Ceiling Lamp Commentation	uuge termenter t	
<mark>Titania TFT panel</mark> TIT-TFT-BUS-S-(3R)	Wall Ceiling Lamp Concerned to the second sec		



Copyright © 2022 TIS, All Rights Reserved TIS Logo is registered trademark of TIS CONTROL. All of the specification are subject to change without notice. TIS CONTROL PTY LIMITED SA , AUSTRALIA TIS CONTROL LIMITED Wanchai, Hong Kong